# CS-LC1C(A0-1F2WPFRL)



#### Introduction

The EZVIZ LC1C is a security camera and outdoor floodlight in one amazing package, meeting your need for both security and night time illumination in the yard, driveway, and more. More than just blasting a combined 2,000 lumens of brightness, the LC1C Camera monitors your surroundings with active defense and real-time motion notifications.

### Main Features



FHD 1080P Resolution



Motion Detection



Two-way Talk



Build-in Siren, 100dB



PIR Motion Detection



Dual Lights, 2000lm



View from Anywhere



MicroSD Slot for Local Storage (Up to 256GB)

### **Dimension**





# Specifications

Model	CS-LC1C(A0-1F2WPFRL)
System parameters	
Processor	High-Performance Embedded SOC Processor
Operation System	Embedded Linux
Light Parameters	
Lamp	2
LED	SMD LED
Brightness	2000LM(+/-10%)
CRI	80
Color Temperature	3000K
Life-span	@B50L70@Ta 25°C 25000H
PIR Sensor Detection	
Detection Distance	Max. 30ft
Detection Range	Max. 270°
Camera Parameters	
Max. Resolution	1920 × 1080
Camera Angel	120° (Diagonal)
IR Range	Max. 25m
Video Parameters	
Compression Standard	H.264/ H.265
Frame Rate	Max. 25 fps, Sel f-a daptive during network transmission
DNR	3D DNR
WDR	Supports
BLC	Supports
Audio Parameters	
Audio Input	Built-in Omni-direction microphone
Audio Output	Built-inloudspeaker
Audio Quality	Nois e SSuppression
Network Parameters	
Wireless	802.11 b/g/n @2.4GHz only (2T2R, Dual-Antenna)
Network Configuration	AP Pairing
Storage	Micro CD cord (Up to 3FCCD)
Local Storage	Micro SD card (Up to 256GB)
Cloud Storage Event	EZVIZ Cloud Storage
Sensor	PIR Detection Sensor
Alarm	Customized Alert Area
General	Customized Field File Ca
Working Temperature	-20°F to 120°F (-30°C to 50°C)
Working Humidity	0-95%
Power Supply	Hardwired(100v-240v)
Power Consumption	≤2W(normal), ≤8W(max)
Ingress Protection Grade	IP65 on camera
ingless Fioteulon Graue	n oo on ameria