

Product description

Model with basic equipment.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Compatible with current mortise locks
- Compatible with ProFix® 2 striking plates
- Optimized sliding ramp for a smooth interplay with latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

Handing	Universal
Noise damped	Yes
Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
Hold-open function	Yes
Continuous duty	11-13 V_DC
Rated resistance	43 Ohm
Current consumption 12 V AC	250 mA
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
current consumption	250 mA
Current consumption AC 12 V	250 mA
Current consumption DC	280 mA
(stabilised)	
Current consumption DC	280 mA
(stabilized) 12 V	
Break-in resistance	3750 N
Height	66 mm
Width	20 mm
Depth	26 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload AC	200 N
Installation position	Vertical and horizontal
Max. latch preload DC (stabilised)	50 N
Load cycles for in-plant test	250000
Suitable for fire doors	No

Article number 128.13B-----A71

EAN-Number 4042203425392

