

VTO6221E-P

Apartment Outdoor Station



Technical Specification

Model	VTO6221E-P
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS

Video

Video Compression	H.264
Image Sensor	1/2.9" 2MP CMOS
Auto Gain Control	White Light
Lens	2mm
Angle of View	H:138°,V:78°, D:158°
Day/Night	Color Image

Audio

Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk

Display

Screen	2.3" OLED
--------	-----------

Operation Mode

Keypad	Mechanical Button with Braille
Reader	Mifare Card (13.56MHz)

Features

- Small size apartment door station
- Supplemental lighting with white light
- 2MP CMOS camera
- Mechanical button with Braille
- Aluminium alloy plate, IK08, IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)
- Door release via password and Mifare card



Interface

Alarm In/Out	1/1
Door Control	1 Relay Out 1 RS485 1 Feedback 1 Exit Button
Wiegand	1


Network

Ethernet	10M/100Mbps
Network Protocol	TCP/IP


General

Ingress Protection	IK08, IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)
Tamper Switch	1
Installation	Surface & Flush
Material	Aluminum
Power	DC 12V, PoE(802.3af)
Power Consumption	Work ≤6W
Working Temperature	-40°C to +60°C
Relative Humidity	20%RH-95%RH
Dimensions	200mm×98mm×32mm
Weight	1.5kg

Dimensions



View Area



Application

