

DH-IPC-HDW2221R-ZS

2MP FHD Network Small IR Dome Camera



- . 1/2.7" 2Megapixel progressive scan CMOS
- . H.264+ & H.264 dual-stream encoding
- . 25/30fps@1080P(1920x1080) & 25/30fps @720P(1280x720)
- . WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- . Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- . 2.7mm~12mm motorized lens
- . Max. IR LEDs Length 60m
- . IP67, PoE



System Overview

The IR Megapixel Vari-focal Eyeball camera delivers 2MP resolution with a motorized 2.7mm – 12mm varifocal lens. The camera's elegant blend of aesthetics combined with a range of easy mounting solutions provides an excellent choice for a variety of small to mid-size applications at an affordable price.

Functions

True Day/Night

A day/night mechanical IR cut filter makes this camera ideal for applications with fluctuating lighting conditions, delivering color images during the day and automatically switching to monochrome as the scene darkens.

Regions of Interest

Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas.

Smart IR

With IR illumination, the camera has the ability to capture detailed images in low light or total darkness. The camera's Smart IR technology adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object. Smart IR technology prevents IR LEDs from whiting out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 60m (197ft).

Wide Dynamic Range

Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. For applications with both bright and low lighting conditions that change quickly, True WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video

Image Flip

Capturing unnecessary data such as surrounding hallway walls can increase storage requirements without any added value. The image flip feature allows the camera's image to be rotated in 90° increments for better video optimization.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust to IP67 standards, making it suitable for indoor or outdoor environments.

Supporting $\pm 25\%$ input voltage tolerance, this camera suits even the most unstable conditions for outdoor applications. Its 8KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Streaming

With a choice of unicast or multicast streaming, bandwidth-efficient viewing, recording and third-party video management can easily be achieved. Dual streaming enables bandwidth-efficient viewing and recording. Depending on the resolution and frame rate selected on the first stream, the second stream provides a copy at a lower resolution.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) and PSIA (Physical Security Interoperability Alliance) specifications, ensuring interoperability between network video products regardless of manufacturer.

Smart H.264+

Delivering high quality video without straining the network, Smart H.264+ is the optimized implementation of H.264. The Smart H.264+ encoding platform includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing a savings of up to 70% of bandwidth and storage when compared with standard H.264.



Technical Specification

Camera

Image Sensor	1/2.7" 2Megapixel progressive scan CMOS
Effective Pixels	1920(H)x1080(V)
RAM/ROM	256M/16M
Scanning System	Progressive
Minimum Illumination	0.1Lux/F1.4(Color); 0Lux/F1.4 (IR on)
S/N Ratio	More than 50dB
IR Distance	Distance up to 60m (197ft)
IR On/Off Control	Auto/ Manual
IR LEDs	2

Lens

Lens Type	Motorized
Mount Type	Board-in
Focal Length	2.7mm~12mm
Max. Aperture	F1.4
Angle of View	H:99°~37°, V:52°~21°
Focus Control	Auto (-ZS) Manual(-VFS)
Close Focus Distance	0.3m

PTZ

Pan/Tilt Range	Pan:0°~360°;Tilt: 0°~78°; Rotation: 0°~360°
----------------	--

Video

Compression	H.264+ / H.264
Streaming Capability	2 Streams
Resolution	1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/CIF(352x288/352x240)
Frame Rate	1080P/720P(1 ~ 25/30fps) D1/CIF(1 ~ 25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H264:40K ~10Mbps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Sunny/Night/Outdoor/Customized
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detetion	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Smart IR	Support
Digital Zoom	16x

Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio

Compression	N/A
-------------	-----

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP;TCP;ARP;RTSP;RTP;UDP;SMTP;FTP;DHCP;DNS;DDNS;PPPOE;IPv4/v6;SNMP;QoS;UPnP;NTP;Bonjour;802.1x;Multicast
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	10 Users/20 Users
Edge Storage	NAS(Network Attached Storage), Local PC for instant recording, 128GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS
Smart Phone	iPhone, iPad, Android Phone

Certifications

Certifications	CE (EN 60950:2000) UL: UL60950-1 FCC: FCC Part 15 Subpart B
----------------	---

Interface

Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A

Electrical

Power Supply	DC12V, PoE (802.3af) (Class 0)
Power Consumption	<7.9W/9.87W

Environmental

Operating Conditions	-30°C~+60°C(-22°F ~ +140°F), Less than 95% RH
Storage Conditions	-30°C~+60°C(-22°F ~ +140°F), Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A

Construction

Casing	Metal
--------	-------

Dimensions	Ø122mm x 104.9mm(4.8" x4.1")
Net Weight	0.59Kg (1.30lb)
Gross Weight	0.71Kg (1.57lb)

Ordering Information

Type	Part Number	Description
2MP camera	DH-IPC-HDW2221RP-ZS	2MP FHD Network Small IR Dome Camera, WDR, PAL
	DH-IPC-HDW2221RN-ZS	2MP FHD Network Small IR Dome Camera, WDR, NTSC
	IPC-HDW2221RP-ZS	2MP FHD Network Small IR Dome Camera, WDR, PAL
	IPC-HDW2221RN-ZS	2MP FHD Network Small IR Dome Camera, WDR, NTSC
Accessories (optional)	PFB203W + PFA152	Pole mount
	PFA137	Junction box

Accessories

Optional:



PFA137
Junction box



PFB203W
Wall mount



PFB203W
Wall mount



PFA152
Pole mount

Junction Mount	Pole Mount
PFA137	PFB203W + PFA152
Wall Mount	
PFB203W	

Dimensions (mm/inch)

