

## DS-KB2411T-IM Four-Wire Analog Door Station



- Hands-free video intercom communication
- Supports two door stations simultaneously in the intercom system
- Self-adaptive IR supplement (with photoresistor)
- One-touch calling
- 2 MP sensor with 960 × 576 stream resolution
- Unlock controlling
- Convenient installation and easy operation

## ▪ Specification

Video parameters	
Camera	1/2.7" CMOS
Resolution	1920 × 1080 Stream resolution: 960 × 576
Video Frame Rate	PAL: 25 fps
FOV	Horizontal: 66.2°, Vertical: 37.2°
Audio parameters	
Audio Input	Built-in omnidirectional microphone
Audio Output	Built-in loudspeaker
Device interfaces	
Four-wire Interface	1 four-wire interface (1-ch video input, 1-ch audio input/output, 1-ch power supply, 1-ch grounding)
I/O Output	1 relay output
General	
Power Supply	12 VDC
Power Consumption	Max. 5W
Working Temperature	-10° C to + 55° C (14° F to 131° F)
Working Humidity	10% to 90%
Dimensions (L x W x H)	135.14 mm × 49.6 mm × 41.93 mm (5.32" × 1.95" × 1.65")
Material	Aluminum alloy

## ▪ Available Model

DS-KB2411T-IM

▪ Dimension

