

### Product description

Model with basic equipment.

### Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

### Scope of delivery

- 1 piece electric strike

### Note

- Not an authorised locking system for doors along escape and rescue routes

### Technical data

|                                    |                         |
|------------------------------------|-------------------------|
| Handing                            | Universal               |
| potential                          | 12 V DC                 |
| Noise damped                       | Yes                     |
| Adjustable keeper (FF, FaFix®)     | Yes                     |
| Fail-unlocked                      | Yes                     |
| Rated operating voltage tolerance  | ± 10 %                  |
| range                              |                         |
| Rated resistance                   | 51 Ohm                  |
| Current consumption 12 V DC        | 235 mA                  |
| Break-in resistance                | 3750 N                  |
| Height                             | 66 mm                   |
| Width                              | 16 mm                   |
| Max. latch preload DC (stabilised) | 30 N                    |
| Depth                              | 26 mm                   |
| FaFix® adjustment range            | 3 mm                    |
| Latch bolt engaging depth          | 5,5 mm                  |
| Operating temperature range        | -15 °C to +40 °C        |
| Installation position              | Vertical and horizontal |
| Load cycles for in-plant test      | 250000                  |
| Suitable for fire doors            | No                      |

|                |               |
|----------------|---------------|
| Article number | 138-----E91   |
| EAN-Number     | 4042203342934 |

