

## DESCRIPTION

The GT-1M3 is an audio/video tenant station for the GT Series Multi-Tenant Video Intercom system. It is equipped with door release and talk buttons. In addition, the station has a concierge/security guard call button and an option button to control external devices, such as lights. The unit also has zoom and a light adjustment button for the camera at the entry. When a visitor calls, the tenant station rings and video is displayed on screen. The call is answered by pushing the talk button. The GT-1M3 has the capability of calling the Concierge/Security Guard station(s), turning on an external light while speaking with a visitor at the entrance, and receiving an emergency tone from a pull cord or panic call button. The GT-1M3 has a slim, streamlined design and can be surface mounted. Two units can be used in the same tenant location. Communication between tenant stations is not possible. Communication is hands-free at the entrance station when a tenant answers the call. While speaking with the visitor, the GT-1M3 can communicate with either hands-free (VOX) or push-to-talk (PTT) functionality.


## GT-1M3 FEATURES

- 3.5" LCD color monitor
- Hands-free audio communication
- Door release button
- Talk button
- Concierge/Security guard call button
- Option button for external devices
- Zoom and brightness control
- Call tone volume control
- Communication volume control

# GT-1M3

## 3.5" Video Tenant Station

### FEATURE CALL-OUT



### FEATURE CALL-OUT DEFINITIONS

- [1] Microphone
- [2] Color LCD video screen
- [3] Door release button
- [4] Adjust button
- [5] Zoom/Wide button
- [6] Speaker
- [7] Concierge/Security guard call/light button
- [8] Option button
- [9] Talk/Off button
- [10] Status indicator (orange)
- [11] Screen brightness control (0-10)
- [12] Receive volume control (0-10)
- [13] Call tone volume control (0-10)

### SPECIFICATIONS

Power Source:	24V DC, supplied from GT-BC
Communication:	Hands-free or Push-to-talk
Screen:	3.5 inch TFT color LCD
Mounting:	Surface wall mount
Temperature:	32-104°F (0-40°C)
Dimensions:	7-1/16" H x 4-15/16" W x 1" D
Weight:	Approx. 0.67 lbs (303g)