



Product description

Model with bipolar protective diode.

Overview of Advantages

- Radius keep, FaFix®, adjustable by 3 mm
- Voltage range
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

DIN direction	Universal
potential	22-42 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
Bi-directional diode	Yes
Continuous duty	22-26 V DC
Rated resistance	200 Ohm
Current consumption 24 V AC	60 mA
Current consumption 24 V DC	120 mA
Break-in resistance	3750 N
Height	66 mm
Width	16 mm
Depth	25,5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Suitable for fire doors	No
Max. latch preload AC	200 N
Max. latch preload DC (stabilised)	50 N
Max. latch preload DC (stabilised)	200 N
	42 V

Article number	11805- - - - - B71
----------------	--------------------

EAN-Number	4042203341272
------------	---------------