

Electric strike for outdoor areas 118WR

Product description

Model with monitoring contact, actuated by the latch bolt.

Overview of Advantages

- Water-proof for use outdoors
- Protection rating IP54 for the electrical components
- Connecting cable 300 mm length
- Equipped with bipolar protective diodes
- Radius keep, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Striking plates with 2 position settings available
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

Adjustable keeper (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-locked	Yes
Bi-directional diode	Yes
Break-in resistance	3750 N
Height	67,3 mm
Width	17,5 mm
Depth	26 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-40 °C to +50 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000

Variants that can be ordered

Order number	Description
118WR-----A71	Without striking plate, 12-24V AC/DC
118WR-----B71	Without striking plate, 22-42 V AC/DC
118WR-----D11	Without strike plate, 6-12 V AC/DC

