

## Product description

Model with adjustable FaFix® latch which features electric strike latch alignment.

## Overview of Advantages

- Suitable for all common striking plates
- Can be mounted DIN right or left by turning over 180°

## Note

- Order code for version DIN right = 14AFF

## Technical data

|                                |                         |
|--------------------------------|-------------------------|
| Adjustable keeper (FF, FaFix®) | Yes                     |
| Fail-locked                    | Yes                     |
| Break-in resistance            | 4000 N                  |
| Height                         | 90 mm                   |
| Width                          | 20 mm                   |
| Depth                          | 28 mm                   |
| Operating temperature range    | -15 °C to +40 °C        |
| Installation position          | Vertical and horizontal |
| Material housing               | Zinc die-cast           |
| Latch material                 | Zinc die-cast           |

## Variants that can be ordered

| Order number | Description  |
|--------------|--|
| 14FF-----D11 | Without face plate, 6-12 V AC/DC                   |
| 14FF-----R11 | Without face plate, 8-16 V AC/DC                   |
| 14FF-----F11 | Without face plate, 24 V AC/DC                     |
| 14FF-----E31 | Without striking plate, 12 V DC electric unlocking |
| 14FF-----F31 | Without striking plate, 24 V DC electric unlocking |
| 14FF-----C31 | Without striking plate, 8V DC electric unlocking   |

