

AXIS M1124 Network Video Camera

Affordable and feature-rich with HDTV 720p

AXIS M1124 is a day and night camera delivering HDTV 720p video in up to 25/30 frames per second. The camera is fitted with an IR-corrected, varifocal and easily exchangeable CS-mount lens with DC-iris. AXIS M1124 includes Axis Zipstream technology that significantly reduces bandwidth and storage requirements. WDR - Forensic Capture provides video optimized for forensic purposes in scenes with complex light conditions. AXIS M1124 supports Power over Ethernet to simplify installation, microSD card slot for edge storage, digital input and output ports for external connection, as well as enhanced capacity for analytic applications such as people counting and heat mapping.

- > [HDTV 720p in up to 25/30 fps](#)
- > [Varifocal CS-mount lens](#)
- > [Day and night camera](#)
- > [WDR - Forensic Capture](#)
- > [Axis Zipstream technology](#)



AXIS M1124 Network Video Camera

| | | | |
|--|--|---|---|
| Camera | | Casing | Polycarbonate blend Color: White NCS S 1002-B and Axis Black NCS S9000-N |
| Image sensor | Progressive scan RGB CMOS 1/3" | Mounting | 1/4"-20 tripod screw thread Camera stand included |
| Lens | Varifocal, IR corrected, CS-mount, DC-iris, 3–10.5 mm Horizontal field of view: 91°–32° Vertical field of view: 49°–18° | Sustainability | PVC-free PCB is bromine-free |
| Day and night | Automatically removable infrared-cut filter | Memory | 512 MB RAM, 256 MB Flash |
| Minimum illumination | Color: 0.25 lux F1.4 B/W: 0.05 lux F1.4 | Power | 8–28 V DC or Power over Ethernet (PoE) IEEE 802.3af Class 2, max 5.0 W, typical 3.6 W |
| Shutter time | 1/66500 to 1 s | Connectors | RJ45 10BASE-T/100BASE-TX PoE Terminal block for one input and one output (12 V DC output, max. load 15 mA) DC input, terminal block |
| Video | | Storage | Support for microSD/microSDHC/microSDXC card SD card encryption Support for recording to network-attached storage (NAS) |
| Video compression | H.264 Baseline, Main and High profile (MPEG-4 Part 10/AVC) Motion JPEG | Operating conditions | -20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing) |
| Resolution | 1280x720 to 160x90 | Storage conditions | -20 °C to 50 °C (-4 °F to 122 °F) Humidity 5–95% RH (non-condensing) |
| Frame rate | Up to 25/30 fps in all resolutions | Approvals | EMC EN 55022 Class A, EN 61000-6-1, EN 61000-3-2, EN 61000-3-3, EN 61000-6-2, EN 55024, EN 50121-4, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN22 Class A, KN24 Safety IEC/EN/UL 60950-1, IS 13252 Environment EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-30, IEC 60068-2-78, IEC 60721-4-3 Class 3M4 Network NIST SP500-267 |
| Video streaming | Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth, VBR/ABR/MBR H.264 | Dimensions | 44 x 70 x 148 mm (1 3/4 x 2 3/4 x 5 13/16 in) |
| Image settings | WDR – forensic capture: up to 120 dB depending on scene, manual shutter time, compression, color, brightness, sharpness, contrast, white balance, exposure control (including automatic gain control), exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, aspect ratio correction, text and image overlay, privacy mask, mirroring of images | Weight | Bare bone: 160 g (0.35 lb) With optics: 200 g (0.45 lb) |
| Pan/Tilt/Zoom | Digital PTZ | Included accessories | AXIS T91A11 Stand White, Installation Guide, Windows® decoder 1-user license |
| Network | | Optional accessories | AXIS T91A04/T91A05 Camera Holders, AXIS T91A50 Telescopic Ceiling Mount, AXIS T92E20 and AXIS T93F Housing Series, Mains adaptor PS-P terminal connector, AXIS T8006 PS12, AXIS T90B Illuminators |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, brute force delay protection, signed firmware | Video management software | AXIS Camera Companion, AXIS Camera Station |
| Supported protocols | IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP | Languages | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| System integration | | Warranty | Axis 3-year warranty and AXIS Extended Warranty option |
| Application Programming Interface | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF® Profile G, ONVIF® Profile S and ONVIF® Profile T. | a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit, and cryptographic software written by Eric Young. | |
| Analytics | Included AXIS Video Motion Detection, active tampering alarm Supported Support for AXIS Camera Application Platform enabling installation of third-party applications | | |
| Event triggers | Analytics, edge storage events, external input | | |
| Event actions | File upload via FTP, HTTP HTTPS, SFTP, network share and email Notification via email, HTTP, HTTPS, TCP Video recording to edge storage, pre- and post-alarm video buffering, PTZ preset, guard tour, send video clip, send SNMP trap, day/night vision mode, WDR mode, status LED indicator, output port | | |
| Data streaming | Event data | | |
| Built-in installation aids | Pixel counter | | |
| General | | | |