

### Product description

Model with mechanical permanent unlocking system in door strike latch and hold-open function.

### Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Compatible with current mortise locks
- Compatible with existing ProFix® 2 striking plates
- Optimized sliding ramp for a smooth interplay with latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

### Scope of delivery

- 1 piece electric strike

### Technical data

Handing	Universal
potential	10-24 V AC/DC
Noise damped	Yes
Adjustable keeper (FF, FaFix®)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Hold-open function (without pin)	Yes
Continuous duty	11-13 V_DC
Rated resistance	43 Ohm
Current consumption 12 V AC	250 mA
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
Break-in resistance	3750 N
Height	66 mm
Width	20 mm
Depth	26 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload AC	200 N
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Max. latch preload DC (stabilised)	50 N
Suitable for fire doors	No
Max. latch preload DC (stabilised)	200 N
24 V	

Article number 148E.13- - - - A71

EAN-Number 4042203428799

