



Network

Купольные

# QNE-8011R

5МП H.265 сетевая камера с плоским куполом и ИК-подсветкой



## Key Features

- Макс. разрешение 5 Мп (2592 x 1944)
- Объектив 2,8 мм с постоянным фокусом
- 0,15 лк (цветн.), 0 лк (Ч/Б, ИК светодиод вкл.)
- До 30 кад/с при 5 Мп (H.265/H.264)
- Поддержка кодеков H.265, H.264, MJPEG, многоканальная передача видео
- Дневной и ночной режимы, WDR (120 дБ)
- Обнаружение внешнего воздействия, движения, расфокусировки, пересечения виртуальной границы
- Слот для карт памяти micro SD/SDHC/SDXC (макс. 128 Гб)
- Функция обзора коридоров, поддержка WiseStream II
- Дальность видимости с ИК подсветкой 20 м
- Функция коррекции искажения объектива, технология PoE

## Compatible Accessories (Optional)



SBV-125BW



SBP-125WMW

# QNE-8011R

5МП H.265 сетевая камера с плоским куполом и ИК-подсветкой



## Specifications

|                           |                                                                                                                                                                                                                                          |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video                     |                                                                                                                                                                                                                                          |
| Imaging Device            | 1/2.8" CMOS                                                                                                                                                                                                                              |
| Resolution                | 5MP mode : 2592x1944, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240<br>4MP mode : 2560x1440, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| Max. Framerate            | H.265/H.264: Max. 30fps/25fps(60Hz/50Hz)<br>MJPEG: Max. 15fps (@5MP Max. 2fps)                                                                                                                                                           |
| Min. Illumination         | Color: 0.15Lux(F2.0, 1/30sec)<br>BW: 0Lux(IR LED on)                                                                                                                                                                                     |
| Lens                      |                                                                                                                                                                                                                                          |
| Focal Length (Zoom Ratio) | 2.8mm fixed focal                                                                                                                                                                                                                        |
| Max. Aperture Ratio       | F2.0                                                                                                                                                                                                                                     |
| Angular Field of View     | H: 104.4° / V: 76.7° / D: 136.1°                                                                                                                                                                                                         |
| Focus Control             | Fixed                                                                                                                                                                                                                                    |
| Pan / Tilt / Rotate       |                                                                                                                                                                                                                                          |
| Pan / Tilt / Rotate Range | 0--350- / 0--75- / 0--360-                                                                                                                                                                                                               |
| Operational               |                                                                                                                                                                                                                                          |
| Camera Title              | Displayed up to 85 characters                                                                                                                                                                                                            |
| Day & Night               | Auto(ICR)                                                                                                                                                                                                                                |
| Backlight Compensation    | BLC, WDR, SDR                                                                                                                                                                                                                            |
| Wide Dynamic Range        | 120dB                                                                                                                                                                                                                                    |
| Digital Noise Reduction   | SSNR                                                                                                                                                                                                                                     |
| Motion Detection          | 4ea, polygonal zones                                                                                                                                                                                                                     |
| Privacy Masking           | 6ea, rectangular zones                                                                                                                                                                                                                   |
| Gain Control              | Low / Middle / High                                                                                                                                                                                                                      |
| White Balance             | ATW / AWC / Manual / Indoor / Outdoor                                                                                                                                                                                                    |
| LDC                       | Support                                                                                                                                                                                                                                  |
| Electronic Shutter Speed  | Minimum / Maximum / Anti flicker (1/5~1/12,000sec)                                                                                                                                                                                       |
| Video Rotation            | Flip, Mirror, Hallway view(90-/270-)                                                                                                                                                                                                     |
| Analytics                 | Motion detection, Tampering, Defocus detection , Virtual area(Intrusion/Enter/Exit), Virtual line(Crossing/Direction)                                                                                                                    |
| Alarm Triggers            | Analytics, Network disconnect                                                                                                                                                                                                            |
| Alarm Events              | File upload via FTP and e-mail<br>Notification via e-mail<br>SD/SDHC/SDXC or NAS recording at event triggers                                                                                                                             |
| IR Viewable Length        | 20m(65.62ft)                                                                                                                                                                                                                             |

|                                   |                                                                                                                                                                                    |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network                           |                                                                                                                                                                                    |
| Ethernet                          | RJ-45(10/100BASE-T)                                                                                                                                                                |
| Video Compression                 | H.265/H.264: Main/High, MJPEG                                                                                                                                                      |
| Smart Codec                       | WiseStream II                                                                                                                                                                      |
| Bitrate Control                   | H.264/H.265: CBR or VBR<br>MJPEG: VBR                                                                                                                                              |
| Streaming                         | Unicast(6 users) / Multicast<br>Multiple streaming(Up to 3 profiles)                                                                                                               |
| Protocol                          | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP |
| Security                          | HTTPS(SSL) Login Authentication<br>Digest Login Authentication<br>IP Address Filtering<br>User access log<br>802.1X Authentication(EAP-TLS, EAP-LEAP)                              |
| Application Programming Interface | ONVIF Profile S/G/T<br>SUNAPI(HTTP API)<br>Wisenet open platform                                                                                                                   |

|                  |                                                                                                                                   |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| General          |                                                                                                                                   |
| Webpage Language | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch |
| Edge Storage     | Micro SD/SDHC/SDXC 1slot 128GB                                                                                                    |
| Memory           | 512MB RAM, 256MB Flash                                                                                                            |

|                                  |                                                                                      |
|----------------------------------|--------------------------------------------------------------------------------------|
| Environmental & Electrical       |                                                                                      |
| Operating Temperature / Humidity | -30°C ~ +55°C(-22°F ~ +131°F) / 0~90% RH<br>* Start up should be done at above -20°C |
| Storage Temperature / Humidity   | -30°C ~ +60°C(-22°F ~ +140°F) / 0~90% RH                                             |
| Certification                    | IP67, IK10                                                                           |
| Input Voltage                    | PoE(IEEE802.3af, Class3)                                                             |
| Power Consumption                | PoE: Max 7.40W, typical 5.50W                                                        |

|                             |                                            |
|-----------------------------|--------------------------------------------|
| Mechanical                  |                                            |
| Color / Material            | White / Aluminum                           |
| RAL Code                    | RAL9003                                    |
| Product Dimensions / Weight | Ø125.0x87.4mm(Ø4.92x3.44"), 645g(1.422 lb) |
| Hanging Mount (Dome)        | SBP-125HMW                                 |
| Backbox                     | SBV-125BW                                  |

|                           |                 |
|---------------------------|-----------------|
| DORI (EN62676-4 standard) |                 |
| Detect (25PPM/ 8PPF)      | 40.2m(131.91ft) |
| Observe (63PPM/ 19PPF)    | 16.1m(52.76ft)  |
| Recognize (125PPM/ 38PPF) | 8.0m(26.38ft)   |
| Identify (250PPM/ 76PPF)  | 4.0m(13.19ft)   |