



# Mars-S1000 Series

Mars-S1000 Single-Lane Speed Gate Mars-S1011 Single-Lane Speed Gate (w/ controller and RFID reader)

Mars-S1022 Single-Lane Speed Gate (w/ controller and fingerprint & RFID readers)







0

U 🖉

e-passage Monitoring Both Directions





#### Anti-co

#### Highly Durable and Low Maintenance Costs

- Modularized structure design
- Exposed mounting holes for easy installation
- Mainly made of SUS304 stainless steel

#### PGIC Controller

- Equipped with a PGIC controller
- Access control
- General features and parameters settings on the controller's menu

### LED Indicator -

- Visual cues for correct walking directionClear guidance
- with green and red illustration







#### Switchable Reader Panel

- Four panels available:
- RFID only
- RFID & Fingerprint
- RFID & QR Code
- RFID & Fingerprint & QR Code
- Reducing middlemen's
- inventory pressureReducing installation time & expenses

#### Installation Place for Facial Recognition A&C Terminals

- Diameter: 34mm
- Integration with Facial Recognition, Temperature and Mask Detection Terminals

#### Infrared Sensors

- 8 pairs of infrared sensors for stronger tailgating detection
- Maximum 12 pairs of sensors could be installed

## Specifications

Model	Mars - S1000 Series
Power Requirements	AC100V to 120V / 200V to 240V, 50 to 60Hz
Working Power	55W; 20W (stand-by)
Drive Unit	Brushless Motor
MCBF	5 millions
Technical Throughput Rate	Up to 30 people per minute
Barrier Movement	Swing
Noise	<60dB
Infrared Sensor	8 pairs (option: ≤12 pairs)
LED Indicator	Support
Working Temperature	-25℃ to 65℃
Working Humidity	20% to 95% (non-condensing)
Working Environment	Indoor / Outdoor (if sheltered)
Lane Width	650mm (option: ≤900mm)
Dimensions (L*W*H)	1360 * 120 * 1020 (mm)
Dimensions with Packaging (L*W*H)	1510 * 365 * 1216 (mm) <i>(2 boxes)</i>
Net Weight	110kg (±5kg)
Gross Weight	160kg (±5kg)
Cabinet Material	SUS304 stainless steel (option: SUS316 stainless steel)
Lid Material	SUS304 stainless steel
Barrier Material	Acrylic (option: glass)
Packing Material	Wooden case
Protection Level	IP34

## Applications



Airports



Government Buildings



Hotels




Gyms



Banks

## Dimensions (mm)





V9.0 2021.05.21