

DS-3E1326P-EI**24 Port Fast Ethernet Smart POE Switch**


- 24 × 100 Mbps PoE RJ45 ports, 2 × gigabit combos.
- IEEE 802.3at/af standard for PoE ports.
- Network topology management, alarm push, network health monitor.
- 6 KV surge protection for PoE ports.
- AF/AT camera can reach up to 300 m in extend mode.

▪ Specification


Model		DS-3E1326P-EI
Network Parameters	Port Type	RJ45 port, full duplex, MDIMDI-X adaptive
	Ports	24 × 10/100 Mbps PoE port, 2 × 1 Gigabit combo
	Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3z
	High Priority Ports	Ports 1 to 8
	Forwarding Mode	Store-and-forward switching
	Working Mode	Standard mode (default), Extend mode
	MAC Address Table	16 K
	Switching Capacity	8.8 Gbps
	Packet Forwarding Rate	6.5472 Mpps
	Internal Cache	4 Mbits
PoE Power Supply	PoE Standard	IEEE 802.3af, IEEE 802.3at
	PoE Power Pin	End-span: 1/2(-), 3/6(+)
		Mid-span: 4/5(+), 7/8(-) 8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
	PoE Port	PoE: Ports 1 to 24
	Max. Port Power	30 W
Software Function	PoE Power Budget	370 W
	Device Maintenance	Support remote upgrade, default parameter restoration, logs viewing, and basic network parameter configuration.
	Port Configuration	Support rate, flow control, and switch configuration
	PoE Configuration	Support port rate configuration, flow control, and ports enabling.
General	Link Aggregation	Support G1, G2 port static link aggregation
	Shell	Metal material
	Net Weight	2.83 kg (6.24 lb)
	Gross Weight	3.800 kg (8.38 lb)
	Dimensions (W × H × D)	440.00 mm × 44.00 mm × 221.00 mm (17.32" × 1.73" × 8.70")
	Operating Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage	-40 °C to 85 °C (-40 °F to 185 °F)

	Temperature	
	Operating Humidity	5% to 95% (no condensation)
	Relative Humidity	5% to 95% (no condensation)
	Power Supply	100-240 VAC, 50/60 Hz, Max. 6.5 A
	Max. Power Consumption	400 W
Approval	EMC	FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016)
	Safety	UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)
	Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No.1907/2006)

▪ Typical Application



▪ Physical Interface




▪ Available Model

DS-3E1326P-EI

DS-3E1326P-EIV2

DS-3E1326P-EIV2/USA

▪ Dimension

▪ **Accessory**

▪ **Optional**

HK-SFP-1.25G-20-1 550 SFP Module	HK-SFP-1.25G-20-1 310 SFP Module	HK-SFP-1.25G-1310 -DF-MM SFP Module	HK-SFP-1.25G-20-1 310-DF SFP Module
			

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq