



Product description

Model with basic equipment. Also useable as a heavy-duty electric strike.

Overview of Advantages

- Radius keep, FaFix®, adjustable by 3 mm
- FaFix® latch adjustable in 0.5 mm increments
- Voltage range
- Symmetrical design. DIN left/right as well as horizontal applicable
- Bipolar diode

Scope of delivery

- 1 piece electric strike

Technical data

DIN direction	Universal
potential	10-24 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
Bi-directional diode	Yes
Continuous duty	11-13 V DC
Rated resistance	43 Ohm
Current consumption 12 V AC	250 mA
Current consumption 12 V DC	280 mA
Current consumption 24 V AC	500 mA
Current consumption 24 V DC	560 mA
Manufacturer's certificate No.	P-120003624
Break-in resistance	9000 N
Height	66 mm
Width	16 mm
Depth	25,5 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	6 mm
Operating temperature range	-15 °C to +40 °C
Load cycles for in-plant test	250000
Installation position	Vertical and horizontal
Suitable for fire doors	Yes
Certified in compliance with	DIN EN 14846:2008
Max. latch preload DC (stabilised) 12 V	50 N
Max. latch preload AC operation 24 V	350 N
Max. latch preload DC (stabilised) 24 V	50 N
Max. latch preload DC (stabilised) 200 N	200 N
Max. latch preload AC	200 N
DIN direction	universal
VdS-approval	Z114003

Article number 118F-----A71

EAN-Number 4042203417434

